



DSL-125A

DSL-125B

PRODUCT FEATURES

 125A Controller	 125B Controller
 125A Motor	 125B Motor
 125A Power Cable	 125B Power Cable
 125A/B Idle Pulley	 125A/B Floor Guide
 125A/B Remote Control	 125A/B Stopper
 125A/B Hangers	 125A/B Belt Bracket
 Belt	 Microwave Sensor

TECHNICAL DATA

Door form: single door / double door

Loading weight: $\leq 1 \times 150\text{kg}$ / $\leq 2 \times 125\text{kg}$

Door width: 750-1600mm/650-1250mm

Power supply: AC 110~220V $\pm 10\%$, 50/60Hz

Power consumption: 65W (125A), 50W (125B)

Opening speed: 150-460mm/S (adjustable)

Closing speed: 130-460mm/S (adjustable)

Open time: 0-8S (adjustable)

Manual force: <40N/ <50N

Temperature range: -20 ~ +50°C

FEATURES

The microcomputer control system drives the motor and controls the door to operate in the set mode. Wide voltage power supply design, many interface such as double door interlock.


Adopting European motor and gearbox integration technology, the drive is strong, the operation is stable, the output power is improved, and it can adapt to the needs of larger doors.

Special lubrication measures, special deceleration mute wheel, professionally designed hanging parts and roller structure greatly reduce the running noise.

Every time there is a self-test procedure, the door will rebound when it encounters resistance, which fully guarantees the safety of the passers-by.

Suitable for office buildings, storefronts, banks, restaurants, hotels, shopping centers, laboratories, hospitals and other places.

SECTIONAL VIEW





DSH-250



PRODUCT FEATURES

 250 Controller	 250 Motor
 250 Idle Pulley	 250 Hangers
 250 Power Cable	 250 Belt Bracket
 250 Cable holder	 250 Floor Guide
 250 Remote Control	 250 Stopper
 Belt	 Microwave Sensor

TECHNICAL DATA

Door form: single door / double door
 Loading weight: $\leq 1 \times 250\text{kg} / \leq 2 \times 200\text{kg}$
 Clean opening width: 1000-2800mm/1800-3800mm
 Power supply: AC 110-220V $\pm 10\%$, 50/60Hz
 Power consumption: $< 100\text{W}$
 Opening speed: 200-460mm/S (adjustable)
 Closing speed: 200-460mm/S (adjustable)
 Open time: 1-9S (adjustable)
 Closed force F: $> 100\text{N}$
 Manual force: $< 100\text{N}$
 Humidity range: $-20 \sim +50^\circ\text{C}$

FEATURES

Intelligent control system, various parameters can be flexibly adjusted by manual or remote control according to the selected controller. Low-noise power unit, motor, worm gear and reducer integrated.

It adopts modern design, applies high-power brushless motor and new mechanical components that are trusted by the world. The hanging parts are made of imported high-strength nylon, and the load capacity of the unit reaches $2 \times 200\text{Kg}$.

The electric lock function is safe and reliable.

The control unit can be connected with building fire center, when fire, the door can be hold open or hold closed for safety.

It is suitable for all kinds of large-channel, industrial workshops, etc. It runs smoothly, is easy to install and easy to maintain.

SECTIONAL VIEW

